



Harmonised Product Standard

EN 14351-1:2006 +A2:2016

Declaration of Performance

Type of construction product:
Entrance doors and Patio doors

Rationel AURAPLUS, triple-glazed

DOP no.:

D-EW-20240513

The performance of the Entrance doors and Patio doors in the product line Rationel AURAPLUS, triple-glazed are in conformity with the declared in the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.
System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:
For domestic and commercial buildings

Manufacturer:

DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):
DANISH TECHNOLOGICAL INSTITUTE
NB1235


Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

06 May 2024

Horsens

Signed on behalf of DOVISTA A/S



Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Declaration Of Performance Rationel AURAPLUS, triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
Opening function								
EDFI	Flush door, inward opening, 1-leaf							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,61 (W/m2K)	-	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-21/2024-Feb.	DTI/202289-21/2024-Feb.	-	-	-	0108/682833R, 2016-02-10	-	DTI/202289-21/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
EDFI-2	Flush door, inward opening, 2-leaf							
Declared value	NPD	NPD	None	N/A	NPD	0,61 (W/m2K)	-	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833R, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-
EDFO	Flush door, outward opening, 1-leaf							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,59 (W/m2K)	-	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-19/2024-Feb.	DTI/202289-19/2024-Feb.	-	-	-	0108/682833R, 2016-02-10	-	DTI/202289-19/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance Rationel AURAPLUS, triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
Opening function								
EDFO-2	Flush door, outward opening, 2-leaf							
Declared value	NPD	NPD	None	N/A	NPD	0,59 (W/m2K)	-	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833R, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-
EDI	Glazed entrance door, inward opening, 1-leaf							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,84 (W/m2K)	g 0,53 / LT 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-21/2024-Feb.	DTI/202289-21/2024-Feb.	-	-	-	0108/682833R, 2016-02-10	-	DTI/202289-21/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
EDI-2	Glazed entrance door, inward opening, 2-leaf							
Declared value	NPD	NPD	None	N/A	NPD	0,84 (W/m2K)	g 0,53 / LT 0,74	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833R, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance Rationel AURAPLUS, triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
Opening function								
EDO	Glazed entrance door, outward opening, 1-leaf							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,81 (W/m2K)	g 0,53 / LT 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-19/2024-Feb.	DTI/202289-19/2024-Feb.	-	-	-	0108/682833R, 2016-02-10	-	DTI/202289-19/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
EDO-2	Glazed entrance door, outward opening, 2-leaf							
Declared value	NPD	NPD	None	N/A	NPD	0,81 (W/m2K)	g 0,53 / LT 0,74	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833R, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-
PDI	Patio door, inward opening, 1-leaf							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,84 (W/m2K)	g 0,53 / LT 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-21/2024-Feb.	DTI/202289-21/2024-Feb.	-	-	-	0108/682833R, 2016-02-10	-	DTI/202289-21/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance Rationel AURAPLUS, triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
Opening function								
PDI-2	Patio door, inward opening, 2-leaf							
Declared value	NPD	NPD	None	N/A	NPD	0,84 (W/m2K)	g 0,53 / LT 0,74	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833R, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-
PDO	Patio door, outward opening, 1-leaf							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,81 (W/m2K)	g 0,53 / LT 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 1235	NB 1235	-	-	-	NB 1235	-	NB 1235
Test report	DTI/202289-19/2024-Feb.	DTI/202289-19/2024-Feb.	-	-	-	0108/682833R, 2016-02-10	-	DTI/202289-19/2024-Feb.
Tested size (mm), WxH	950 x 2185	950 x 2185	-	-	-	1230 x 2180	-	950 x 2185
PDO-2	Patio door, outward opening, 2-leaf							
Declared value	NPD	NPD	None	N/A	NPD	0,81 (W/m2K)	g 0,53 / LT 0,74	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/682833R, 2016-02-10	-	-
Tested size (mm), WxH	-	-	-	-	-	1230 x 2180	-	-

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Declaration Of Performance Rationel AURAPLUS, triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
Opening function								
SD Sliding door								
Declared value	NPD	NPD	None	N/A	NPD	1,01 (W/m2K)	g 0,49 / LT 0,71	NPD
Classification standard	-	-	-	-	-	-	-	-
Test standard	-	-	-	-	-	EN ISO 10077-2: 2003/2012	-	-
Notified body	-	-	-	-	-	NB 1235	-	-
Test report	-	-	-	-	-	0108/581248, 2013-11-26	-	-
Tested size (mm), WxH	-	-	-	-	-	2500 x 2180	-	-

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.