



Harmonised Product Standard

**EN 14351-1:2006+A2:2016**

## **Declaration of Performance**

Type of construction product:  
Entrance doors and Patio doors

**Rationel FORMA  
double-glazed**

DOP nr.:  
**D-EM-20260201**

The performance of the Entrance doors and Patio doors in the product line Rationel FORMA double-glazed are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:  
(AVCP) System 3

Intended use:  
For domestic and commercial

Manufacturer:  
**DOVISTA A/S**

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):  
NB 1235 - Technological Institute, Denmark

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

26 januar 2026

---

Horsens

Signed on behalf of DOVISTA A/S



---

Allan Lindhard Jørgensen  
CEO, DOVISTA A/S

| Opening function                                              | 4.2                    | 4.5                    | 4.6                  | 4.8                                     | 4.11                 | 4.12                                | 4.13                   | 4.14                   |
|---------------------------------------------------------------|------------------------|------------------------|----------------------|-----------------------------------------|----------------------|-------------------------------------|------------------------|------------------------|
|                                                               | Resistance to windload | Water tightness        | Dangerous substances | Load bearing capacity of safety devices | Acoustic performance | * Thermal transmittance coefficient | * Radiation properties | Air permeability       |
| <b>EDFI              Flush door, inward opening, 1-leaf</b>   |                        |                        |                      |                                         |                      |                                     |                        |                        |
| Declared value                                                | Class C4 (1600 Pa)     | Class 9A (600 Pa)      | None                 | N/A                                     | NPD                  | 0,61 (W/m2K)                        | -                      | Class 4 (±600 Pa)      |
| Classification standard                                       | EN 12210:2016          | EN 12208:2016          | -                    | -                                       | -                    | -                                   | -                      | EN 12207:2016          |
| Test standard                                                 | EN 12211:2016          | EN 1027:2016           | -                    | -                                       | -                    | EN ISO 10077-2: 2003/2012           | -                      | EN 1026:2016           |
| Notified body                                                 | NB 1235                | NB 1235                | -                    | -                                       | -                    | NB 1235                             | -                      | NB 1235                |
| Test report                                                   | DTI/244214-6/2024-Sep. | DTI/244214-6/2024-Sep. | -                    | -                                       | -                    | 0108/678451R, 2016-01-08            | -                      | DTI/244214-6/2024-Sep. |
| Tested size (mm), WxH                                         | 950 x 2185             | 950 x 2185             | -                    | -                                       | -                    | 1230 x 2180                         | -                      | 950 x 2185             |
| <b>EDFI-2              Flush door, inward opening, 2-leaf</b> |                        |                        |                      |                                         |                      |                                     |                        |                        |
| Declared value                                                | Class C4 (1600 Pa)     | Class 9A (600 Pa)      | None                 | N/A                                     | NPD                  | 0,61 (W/m2K)                        | -                      | Class 4 (±600 Pa)      |
| Classification standard                                       | EN 12210:2016          | EN 12208:2016          | -                    | -                                       | -                    | -                                   | -                      | EN 12207:2016          |
| Test standard                                                 | EN 12211:2016          | EN 1027:2016           | -                    | -                                       | -                    | EN ISO 10077-2: 2003/2012           | -                      | EN 1026:2016           |
| Notified body                                                 | NB 1235                | NB 1235                | -                    | -                                       | -                    | NB 1235                             | -                      | NB 1235                |
| Test report                                                   | DTI/244213-4/2024-Jun. | DTI/244213-4/2024-Jun. | -                    | -                                       | -                    | 0108/678451R, 2016-01-08            | -                      | DTI/244213-4/2024-Jun. |
| Tested size (mm), WxH                                         | 1880 x 2185            | 1880 x 2185            | -                    | -                                       | -                    | 1230 x 2180                         | -                      | 1880 x 2185            |
| <b>EDFO              Flush door, outward opening, 1-leaf</b>  |                        |                        |                      |                                         |                      |                                     |                        |                        |
| Declared value                                                | Class C4 (1600 Pa)     | Class 9A (600 Pa)      | None                 | N/A                                     | NPD                  | 0,59 (W/m2K)                        | -                      | Class 4 (±600 Pa)      |
| Classification standard                                       | EN 12210:2016          | EN 12208:2016          | -                    | -                                       | -                    | -                                   | -                      | EN 12207:2016          |
| Test standard                                                 | EN 12211:2016          | EN 1027:2016           | -                    | -                                       | -                    | EN ISO 10077-2: 2003/2012           | -                      | EN 1026:2016           |
| Notified body                                                 | NB 1235                | NB 1235                | -                    | -                                       | -                    | NB 1235                             | -                      | NB 1235                |
| Test report                                                   | DTI/244211-1/2024-May  | DTI/244211-1/2024-May  | -                    | -                                       | -                    | 0108/678451R, 2016-01-08            | -                      | DTI/244211-1/2024-May  |
| Tested size (mm), WxH                                         | 1200 x 2400            | 1200 x 2400            | -                    | -                                       | -                    | 1230 x 2180                         | -                      | 1200 x 2400            |

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

| Opening function                                               | 4.2                    | 4.5                    | 4.6                  | 4.8                                     | 4.11                 | 4.12                                | 4.13                   | 4.14                   |
|----------------------------------------------------------------|------------------------|------------------------|----------------------|-----------------------------------------|----------------------|-------------------------------------|------------------------|------------------------|
|                                                                | Resistance to windload | Water tightness        | Dangerous substances | Load bearing capacity of safety devices | Acoustic performance | * Thermal transmittance coefficient | * Radiation properties | Air permeability       |
| <b>EDFO-2      Flush door, outward opening, 2-leaf</b>         |                        |                        |                      |                                         |                      |                                     |                        |                        |
| Declared value                                                 | Class C4 (1600 Pa)     | Class 7A (300 Pa)      | None                 | N/A                                     | NPD                  | 0,59 (W/m2K)                        | -                      | Class 4 (±600 Pa)      |
| Classification standard                                        | EN 12210:2016          | EN 12208:2016          | -                    | -                                       | -                    | -                                   | -                      | EN 12207:2016          |
| Test standard                                                  | EN 12211:2016          | EN 1027:2016           | -                    | -                                       | -                    | EN ISO 10077-2: 2003/2012           | -                      | EN 1026:2016           |
| Notified body                                                  | NB 1235                | NB 1235                | -                    | -                                       | -                    | NB 1235                             | -                      | NB 1235                |
| Test report                                                    | DTI/244214-1/2024-Sep. | DTI/244214-1/2024-Sep. | -                    | -                                       | -                    | 0108/678451R, 2016-01-08            | -                      | DTI/244214-1/2024-Sep. |
| Tested size (mm), WxH                                          | 2337 x 2400            | 2337 x 2400            | -                    | -                                       | -                    | 1230 x 2180                         | -                      | 2337 x 2400            |
| <b>EDI      Glazed entrance door, inward opening, 1-leaf</b>   |                        |                        |                      |                                         |                      |                                     |                        |                        |
| Declared value                                                 | Class C4 (1600 Pa)     | Class 9A (600 Pa)      | None                 | N/A                                     | NPD                  | 1,28 (W/m2K)                        | g 0,64 / LT 0,82       | Class 4 (±600 Pa)      |
| Classification standard                                        | EN 12210:2016          | EN 12208:2016          | -                    | -                                       | -                    | -                                   | -                      | EN 12207:2016          |
| Test standard                                                  | EN 12211:2016          | EN 1027:2016           | -                    | -                                       | -                    | EN ISO 10077-2: 2003/2012           | -                      | EN 1026:2016           |
| Notified body                                                  | NB 1235                | NB 1235                | -                    | -                                       | -                    | NB 1235                             | -                      | NB 1235                |
| Test report                                                    | DTI/332468-1/2025-Sep. | DTI/332468-1/2025-Sep. | -                    | -                                       | -                    | 0108/678451R, 2016-01-08            | 0108/678451R, 2016     | DTI/332468-1/2025-Sep. |
| Tested size (mm), WxH                                          | 1200 x 2400            | 1200 x 2400            | -                    | -                                       | -                    | 1230 x 2180                         | -                      | 1200 x 2400            |
| <b>EDI-2      Glazed entrance door, inward opening, 2-leaf</b> |                        |                        |                      |                                         |                      |                                     |                        |                        |
| Declared value                                                 | Class B4 (1600 Pa)     | Class 9A (600 Pa)      | None                 | N/A                                     | NPD                  | 1,28 (W/m2K)                        | g 0,64 / LT 0,82       | Class 4 (±600 Pa)      |
| Classification standard                                        | EN 12210:2016          | EN 12208:2016          | -                    | -                                       | -                    | -                                   | -                      | EN 12207:2016          |
| Test standard                                                  | EN 12211:2016          | EN 1027:2016           | -                    | -                                       | -                    | EN ISO 10077-2: 2003/2012           | -                      | EN 1026:2016           |
| Notified body                                                  | NB 1235                | NB 1235                | -                    | -                                       | -                    | NB 1235                             | -                      | NB 1235                |
| Test report                                                    | DTI/332468-2/2025-Sep. | DTI/332468-2/2025-Sep. | -                    | -                                       | -                    | 0108/678451R, 2016-01-08            | 0108/678451R, 2016     | DTI/332468-2/2025-Sep. |
| Tested size (mm), WxH                                          | 2400 x 2400            | 2400 x 2400            | -                    | -                                       | -                    | 1230 x 2180                         | -                      | 2400 x 2400            |

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

|                                                                               | 4.2<br>Resistance to<br>windload | 4.5<br>Water tightness | 4.6<br>Dangerous<br>substances | 4.8<br>Load bearing capacity<br>of safety devices | 4.11<br>Acoustic<br>performance | 4.12<br>* Thermal<br>transmittance<br>coefficient | 4.13<br>* Radiation<br>properties | 4.14<br>Air permeability |
|-------------------------------------------------------------------------------|----------------------------------|------------------------|--------------------------------|---------------------------------------------------|---------------------------------|---------------------------------------------------|-----------------------------------|--------------------------|
| Opening function                                                              |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| <b>EDO                    Glazed entrance door, outward opening, 1-leaf</b>   |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value                                                                | Class C4 (1600 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,26 (W/m2K)                                      | g 0,64 / LT 0,82                  | Class 4 (±600 Pa)        |
| Classification standard                                                       | EN 12210:2016                    | EN 12208:2016          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2016            |
| Test standard                                                                 | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | -                                 | EN 1026:2016             |
| Notified body                                                                 | NB 1235                          | NB 1235                | -                              | -                                                 | -                               | NB 1235                                           | -                                 | NB 1235                  |
| Test report                                                                   | DTI/268669-3/2024-Okt.           | DTI/268669-3/2024-Okt. | -                              | -                                                 | -                               | 0108/678451R, 2016-01-08                          | 0108/678451R, 2016                | DTI/268669-3/2024-Okt.   |
| Tested size (mm), WxH                                                         | 1200 x 2400                      | 1200 x 2400            | -                              | -                                                 | -                               | 1230 x 2180                                       | -                                 | 1200 x 2400              |
| <b>EDO-2                    Glazed entrance door, outward opening, 2-leaf</b> |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value                                                                | Class B4 (1600 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,26 (W/m2K)                                      | g 0,64 / LT 0,82                  | Class 4 (±600 Pa)        |
| Classification standard                                                       | EN 12210:2016                    | EN 12208:2016          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2016            |
| Test standard                                                                 | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | -                                 | EN 1026:2016             |
| Notified body                                                                 | NB 1235                          | NB 1235                | -                              | -                                                 | -                               | NB 1235                                           | -                                 | NB 1235                  |
| Test report                                                                   | DTI/244214-2/2024-Sep.           | DTI/244214-2/2024-Sep. | -                              | -                                                 | -                               | 0108/678451R, 2016-01-08                          | 0108/678451R, 2016                | DTI/244214-2/2024-Sep.   |
| Tested size (mm), WxH                                                         | 2337 x 2400                      | 2337 x 2400            | -                              | -                                                 | -                               | 1230 x 2180                                       | -                                 | 2337 x 2400              |
| <b>PDI                    Patio door, inward opening, 1-leaf</b>              |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value                                                                | Class C4 (1600 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,28 (W/m2K)                                      | g 0,64 / LT 0,82                  | Class 4 (±600 Pa)        |
| Classification standard                                                       | EN 12210:2016                    | EN 12208:2016          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2016            |
| Test standard                                                                 | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | -                                 | EN 1026:2016             |
| Notified body                                                                 | NB 1235                          | NB 1235                | -                              | -                                                 | -                               | NB 1235                                           | -                                 | NB 1235                  |
| Test report                                                                   | DTI/352263-1/2026-Jan.           | DTI/352263-1/2026-Jan. | -                              | -                                                 | -                               | 0108/678451R, 2016-01-08                          | 0108/678451R, 2016                | DTI/352263-1/2026-Jan.   |
| Tested size (mm), WxH                                                         | 1200 x 2400                      | 1200 x 2400            | -                              | -                                                 | -                               | 1230 x 2180                                       | -                                 | 1200 x 2400              |

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

| Opening function                         | 4.2<br>Resistance to<br>windload | 4.5<br>Water tightness | 4.6<br>Dangerous<br>substances | 4.8<br>Load bearing capacity<br>of safety devices | 4.11<br>Acoustic<br>performance | 4.12<br>* Thermal<br>transmittance<br>coefficient | 4.13<br>* Radiation<br>properties | 4.14<br>Air permeability |
|------------------------------------------|----------------------------------|------------------------|--------------------------------|---------------------------------------------------|---------------------------------|---------------------------------------------------|-----------------------------------|--------------------------|
| PDI-2Patio door, inward opening, 2-leaf  |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value                           | Class B4 (1600 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,28 (W/m2K)                                      | g 0,64 / LT 0,82                  | Class 4 (±600 Pa)        |
| Classification standard                  | EN 12210:2016                    | EN 12208:2016          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2016            |
| Test standard                            | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | -                                 | EN 1026:2016             |
| Notified body                            | NB 1235                          | NB 1235                | -                              | -                                                 | -                               | NB 1235                                           | -                                 | NB 1235                  |
| Test report                              | DTI/352263-2/2026-Jan.           | DTI/352263-2/2026-Jan. | -                              | -                                                 | -                               | 0108/678451R, 2016-01-08                          | 0108/678451R, 2016                | DTI/352263-2/2026-Jan.   |
| Tested size (mm), WxH                    | 2400 x 2400                      | 2400 x 2400            | -                              | -                                                 | -                               | 1230 x 2180                                       | -                                 | 2400 x 2400              |
| PDOPatio door, outward opening, 1-leaf   |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value                           | Class C4 (1600 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,26 (W/m2K)                                      | g 0,64 / LT 0,82                  | Class 4 (±600 Pa)        |
| Classification standard                  | EN 12210:2016                    | EN 12208:2016          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2016            |
| Test standard                            | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | -                                 | EN 1026:2016             |
| Notified body                            | NB 1235                          | NB 1235                | -                              | -                                                 | -                               | NB 1235                                           | -                                 | NB 1235                  |
| Test report                              | DTI/244213-1/2024-Jun.           | DTI/244213-1/2024-Jun. | -                              | -                                                 | -                               | 0108/678451R, 2016-01-08                          | 0108/678451R, 2016                | DTI/244213-1/2024-Jun.   |
| Tested size (mm), WxH                    | 1200 x 2400                      | 1200 x 2400            | -                              | -                                                 | -                               | 1230 x 2180                                       | -                                 | 1200 x 2400              |
| PDO-2Patio door, outward opening, 2-leaf |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value                           | Class B4 (1600 Pa)               | Class 7A (300 Pa)      | None                           | N/A                                               | NPD                             | 1,26 (W/m2K)                                      | g 0,64 / LT 0,82                  | Class 4 (±600 Pa)        |
| Classification standard                  | EN 12210:2016                    | EN 12208:2016          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2016            |
| Test standard                            | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | -                                 | EN 1026:2016             |
| Notified body                            | NB 1235                          | NB 1235                | -                              | -                                                 | -                               | NB 1235                                           | -                                 | NB 1235                  |
| Test report                              | DTI/244211-4/2024-May            | DTI/244211-4/2024-May  | -                              | -                                                 | -                               | 0108/678451R, 2016-01-08                          | 0108/678451R, 2016                | DTI/244211-4/2024-May    |
| Tested size (mm), WxH                    | 2337 x 2400                      | 2337 x 2400            | -                              | -                                                 | -                               | 1230 x 2180                                       | -                                 | 2337 x 2400              |

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S